



Xilin
CBD15W-E

China

onQ-30742

WAREHOUSE MOVERS & LIFTS - PALLET MOVERS
NEW - SALE

Date Listed	28 Apr 2023
Reference	CBD15W-E
Power Type	Battery Electric
Lift Capacity	1,500 kg(3,307 lb)
Fork Height	200 mm(8 in)
Tyre Type	Polyurethane / Vulkollan
Weight	205 kg(452 lb)
Machine Height	1,250 mm(49 in)

ADDITIONAL INFORMATION

Adopting floating balance wheel can prevent the side swing of the truck when travelling. Travel smoothly and no swing; great anti-vibration. The whole balance wheel can be removed, easy to maintain. The rock arm mechanism integral structure which improves the structure strength effectively, meanwhile, share and adjust the even force from the fork. Reduce the obvious deflection in fork height after a long use and when loading. The drive wheel adopts horizontal type structure which makes the layout position of the motor higher off the ground to prevent the waterdust and greasy dirt gluing on the motor effectively and improve working condition of the motor. The truck is equipped with a height limit switch. Cut off the lifting circuit when lifting height approaches the highest point to disconnect the power of the hydraulic power unit to prevent the noise from the spillover of the hydraulic station and save the energy caused by spillover.