

Xilin CQD20H China

onQ-30928

WAREHOUSE MOVERS & LIFTS - REACH TRUCKS & STACKERS

NEW - SALE Date Listed Reference Power Type Lift Capacity Mast Type Maximum Lift Height Tyre Type Machine Height (Mast Lowered) Machine Features

28 Apr 2023 CQD20H Battery Electric 2,000 kg(4,409 lb) Triplex (3 Stage) 12,000 mm(472 in) Polyurethane / Vulkollan

4,790 mm(189 in)

Mast full free lift Moving mast Sit down Overhead Guard Fork positioner Side shift

ADDITIONAL INFORMATION

Standard • AC control system. • Powering steering system (EPS). (standard for 10-12m, Option for 8-9.5m) • Electronic multi-valve. • Multi-function display can show: Brake status, Driving direction, Hour meter, Driving speed, Fault code, etc. • Finger-tip control stick. (standard for 10-12m, option for 8-9.5m) • Adjustable speed for forks lifting/lowering mast forward/backward and side shift right/left. • German ZF brand gear box. • Adjustable steering wheel. • With traveling speed limited device when forks at high level. • Electronic height limited device. • Use "H" type mast steel is imported from Germany. • Use double controllers to realize stepless speed regulation of sideshift , both lifting and traveling. • Have safety traveling speed limited device in the mast. Option • Side shift. • Height selection and height position system. • LCD display and camera (LCD for cold storage are available). • EX explosion proof type. • Travel/back-up flashing lights.