

Xilin FB20R

China

onQ-32580

FORKLIFTS - COUNTER BALANCE ELECTRIC

NEW - SALE Date Listed Reference Power Type Lift Capacity Mast Type Maximum Lift Height Tyre Type Machine Height (Mast Lowered) Machine Features

28 Apr 2023 FB20R Battery Electric 2,000 kg(4,409 lb) Triplex (3 Stage) 6,000 mm(236 in) Solid / Puncture Proof

2,610 mm(103 in)

Mast full free lift Overhead Guard 4 wheels Front wheel drive Charger Side shift

ADDITIONAL INFORMATION

SAFETY AND STABILITY Most popular H type driving axle, optimized structure layout and improved efficiency. High power and large torque AC driving motor, large diameter body to export larger torque, heat radiating groove reserved for better heat exchange in case of extra-long-time use. Multifunctional display with using time, fault code, battery status, forklift running information. AC driving motor without brush, free of maintenance; low electric current, silent driving. Low gravity center thanks to relocated battery, greatly reinforcing steering stability. Steering circuit preference, to ensure safety in every turn when steering and lifting in the same time, and to save energy. Dual-controller design, one driving controller, the other control steering and lifting. Metal housing for better protection. Full LED light. ERGONOMICS Optimized structure creates a large and comfortable operating room. Adjustable steering wheel column, the driver can adjust the position according to his need. Integrated light switch and steering wheel. Clear and wide view mast with good visibility. Intelligent mast collapse buffering. SERVICE ABILITY Easy maintained controller and steering potentiometer. Brushless lifting and driving motor, reduced cost of ownership; external encoder, easy to replace and service. Over discharge protecting system: while the battery discharges less than 20%, the instrument warming light will turn on. Braking oil cup installed on the instrument panel, convenient to check and add braking oil. OPTIONAL Sideway battery box Electromagnetic valve Shock-absorbing chair, with power disconnect function Dual-front-wheels Adjustable lifting motor speed system Cold storage application Lithium battery